

The HL-i Series compact design makes it highly suitable for weighing applications at work, school, home or anywhere.

by **AND**  
A&D MERCURY PTY LTD



### HIGHLIGHTS

- **High Weighing Resolution of 1/2,000**  
Precision weighing of 200g x 0.1g for HL-200i and 2000g x 1g for HL-2000i
- **Calibration Function**  
Easy and simple to calibrate the scale with external calibration mass for accurate weighing
- **Multi Weighing Units**  
Meet any weighing application with weighing units of g, oz, ct and tael for HL-200i and g, oz, lb-oz and teal for HL-2000i
- **Two Way Power**  
Use either 4 x AA batteries or the optional AC adaptor
- **Long Battery Life**  
Continuous operation for 1000 hours using alkaline batteries
- **Tare Function to Full Weighing Capacity**  
One touch tare using the "RE-ZERO" key enables the user to use a weighing container and still benefit from the full weighing range of the scale!
- **Large LCD Display**  
Easy to read 13.5mm LCD display
- **Large Weighing Pan**  
Easily weigh large objects on the 130mm diameter weighing pan
- **Auto Power Off Function**  
Save battery life with the Auto Power Off function. HL-i automatically shuts down after 5 minutes of disuse
- **Low Battery Indication**  
Low battery warning is displayed when the batteries are running low
- **Overload Indication**  
Display indicator for scale overload conditions
- **Stable Indicator**  
Lets you know when the scale is stable and ready to weigh ensuring accurate weighing results
- **Compact Size**  
Small size means it's easy to use anywhere. The scale can also be stored on its side or rear, saving space!

### SPECIFICATIONS

	HL-200i	HL-2000i
Capacity x Resolution	200g x 0.1g	2,000 g x 1g
	7.05oz x 0.01oz	70.5oz x 0.1oz
	1000.0ct x 0.5ct	4lb 6.6oz x 0.1oz
	5.335tl x 0.005tl <sup>1</sup>	53.35tl x 0.05tl <sup>1</sup>
Non-Linearity	±0.2g	±2g
Repeatability	0.1g	1g
Span Drift	±0.015%/°C Typical (5°C~35°C)	
Operating Temp.	-10°C~40°C, Less Than 85% RH	
Display	13.5mm, 7-Segment Liquid Crystal Display	
Display Update	Approximately 5 Times per Second	
Power	4 x "AA" Size Batteries or AC Adaptor	
Battery Life	Approximately 1,000 Hours with Alkaline Cells at 20°C	
Pan Size	Ø130mm	
Dimensions	130mm(W)x192mm(D)x51mm(H)	
Weight	Approximately 500g	
Calibration Weight	200g	2,000g
Option	AC Adaptor	

<sup>1</sup> tl : Taiwan tael

### OPTIONS

- AX-TB-196: AC100V with A Plug
- AX-TB-202: AC120V with A Plug
- AX-TB-164: AC220-230V with C Plug
- AX-TB-173: AC220-230V with BF Plug
- AX-TB-172: AC220-240V with S Plug

**Accuweigh Pty Ltd**

WESTERN AUSTRALIA (HEAD OFFICE):  
PHONE: (08) 9259 5535

SOUTH AUSTRALIA OFFICE:  
PHONE: (08) 8447 5011

NEW SOUTH WALES (SYDNEY) OFFICE:  
PHONE: (02) 9728 4877



[www.accuweigh.com.au](http://www.accuweigh.com.au)

VICTORIA OFFICE:  
PHONE: (03) 9548 5554

NEW SOUTH WALES (NEWCASTLE) OFFICE:  
PHONE: (02) 4966 8900

QUEENSLAND OFFICE:  
PHONE: (07) 3265 5520