

Standard Specification								
Specs	Sealing speed	Heater (W)	Drive (kW)		Power (kW)			
	Range	Capacity	Sealer	Sewer				
KS-S	6~10m/min	-	0.4	0.4	1			
KS-23		500×6	0.4		0.4	4		
KS-23D								
KS-24		500×8	0.4			0.4	5	
KS-24D								
KS-26		500×12	0.75				0.4	7.5
KS-26D								

Standard Specification						
Specs	Dimensions (mm)		Weight (kg)	Options		Applications
	Length	Width		Dust cleaner	Crepe tape	
KS-S	1,320	1,110	ca.250	-	standard equipment	Crepe tape only
KS-23	2,240	1,290	ca.420	-		Flat 3 paper plies with innermost ply PE film seal.
KS-23D	2,560	1,290	ca.450	○		Flat 4 paper plies with inner ply seal.
KS-24	2,450	1,290	ca.450	-		Flat 6 paper plies and gusseted 3 paper plies with inner ply seal.
KS-24D	2,770	1,290	ca.500	○		
KS-26	2,910	1,290	ca.520	-		
KS-26D	3,230	1,290	ca.600	○		

• Temp. adjust range 0 to 400°C • Air req. 200NL/min (at 0.5MPa) Pressure 0.5Mpa (5kg/cm²) (varies with speed)

• Sealer height adjust range 800~1400mm

• Add 0.55KW (50Hz) or 0.72KW (60Hz) power when optional dust cleaner is installed.

• Above speeds are not guaranteed ones. They are given for reference only.

• Length of the machine (L) varies slightly between manual insertion type and packaging machine coupling type.

KS: Kraft sealer 2 : Rear sewer □ : Heater pairs D : Dust cleaner
S : Crepe tape + sewer only (KS-S only)