

RINSTRUM R320 DIGITAL INDICATOR

HIGHLIGHTS

- NMI Trade-Approved 4,000 Divisions
- Compact ABS Housing
- Internal Batteries
- RS-232 Serial Output
- Special Functions
- 20mm LCD Display
- Bright LED Backlighting



FEATURES

The Rinstrum 320 digital weight indicator offers high levels of performance and functionality by combining all the very latest advances in weighing technology into one compact package.

A powerful 24 bit Sigma-Delta A/D converter ensures fast and accurate weight readings are attained. The four layer, surface mount PCB has a low power consumption and offers extreme durability under harsh operating conditions.

All Rinstrum models will have a long market life due to the use of FLASH ROMs which allows infield updating to the later software revisions or to accept custom functions.

Another innovation is the Rinstrum "rin-LINK" - a dedicated optical data coupling that connects to the inbuilt IR port on the indicator display for PC access to all setup and calibration functions.

The cosmetically appealing ABS housing design incorporates provision for pole mounting, anti-skid feet for desk mounting and an integral battery compartment for portable and stand-alone uses.

A 20mm, 6 digit LCD display has super-bright LED back-lighting for easy reading under all conditions, including bright sunlight. The backlighting LEDs use a new matrix design for very even light distribution.

The silicon keypad is extremely operator friendly; the operation is light and responsive with both tactile and audible feedback.

The blank keypad button controls the special functions; such as counting, totalising, peak-hold, etc. Labels are supplied to name the function of this key for the operator.

The R320 can power up to 4 x 350Ω loadcells and is software selectable for either 4 wire or 6 wire operation (sense wire linking is not required).

The comprehensive setup and calibration functions are displayed in plain English messages for easy configuration. The software auto-detects the type of power input (plug-pack or internal batteries) and alters the power saving functions accordingly.

An on-board clock/calendar/ram ensures zero, tare, totals and other critical data is not lost or corrupted.

The RS-232 serial output is rated to 15kV static protection and can be set for automatic, network or printing functions. There are two setpoint outputs available for high/low level control applications.

The "rin-VIEW" software allows PC access to all indicator functions and the ability for the setup and calibration data to be saved, restored or copied into other R320's at any time.

STANDARD FEATURES

- OIML and NMI Trade Approved for 4,000 Divisions
- 30,000 Divisions @ 20 Updates per Second
- 5 Points Linearity Correction
- Battery Backed RAM for Zero, Tare, etc.
- Clock and Calendar On-Board
- rin-LINK Connectivity
- 20mm LCD Display with LED Backlighting
- 12-24VDC Power Input
- 4 and 6 Wire Loadcell Wiring
- Spring Loaded, Screwless Cable Terminations
- 2 Isolated Transistor Outputs
- lb/kg Switching, Counting, Totalising, Live Weight, Hold and Peak Hold

SPECIFICATIONS

PERFORMANCE	
Display	LCD with 6 x 20mm High Digits
Back-Light	LED Back-Lighting
Display Resolution	Up to 30,000 Divisions, Minimum of 0.25 μ V/Division (Trade-Approved 4,000 Divisions at 0.8 μ V/Division)
Count-by	1, 2, 5, 10, 20, 50, 100 (Entered in Display Weight)
Zero Cancellation	\pm 2.0mV/V
Span Adjustment	0.1mV to 3.0mV Full Scale
Stability/Drift	Zero: <0.1 μ V/ $^{\circ}$ C, Span <10ppm/ $^{\circ}$ C, Linearity <20ppm, Noise <0.05 μ V p-p
Operating Environment	Temperature -10 $^{\circ}$ C to +50 $^{\circ}$ C, Humidity < 90% Non-Condensing
DIGITAL	
Setup and Calibration	Full Digital with Visual Prompting in Plain Messages
Memory Retention	Full Non-Volatile Operation
Digital Filter	Sliding Window Average from 0.1 to 4.0 Seconds
Zero Button	Adjustable from \pm 2% to \pm 20% of Full Capacity
A/D CONVERTOR	
Type	24 Bit Sigma Delta
Resolution	8,388,608 Internal Counts
A/D Sync Filter	20Hz, FIR Filter >80dB
LOADCELLS	
Excitation	5V for Up to 4 x 350 Ω Loadcells (6-Wire and Shield)
Loadcell Connection	6-Wire and Shield (Intrinsic Safety-Barrier Compatible)
SERIAL COMMS	
Serial Output	Single RS-232 as Automatic Transmit, Network or Printer Drive
OPTI-LINK	By-Directional Isolated Infra-Red to RS-232 PC Link
DIMENSIONS	
Body Size	Desk Stand: 164mm(L) x 75mm(H) x 83mm(D)
	Panel Mount: 164mm(L) x 75mm(H) x 28mm(D)
Panel Cutout	120mm x 60mm Rectangular Cutout
POWER SUPPLY	
Standard	12 to 24VDC (2.5VA Maximum) ON/OFF Key with Memory Feature
Variants	AC Plug Pack: 110/240VAC 50/60Hz in 12VDC 0.5A Out 4 x AA Batteries (Alkaline or Rechargeable NiMH, NiCad, etc.)
FEATURES	
Additional Features	Five Point Linearity Correction Assignable Function Key for Operator Use (Functions Include Unit Switching, Counting, Manual Hold, Peak Hold and Livestock Weighing) 2 x Isolated Transistor Drive Outputs (Open-Emitter) Battery Backed Clock and Calendar
Approvals	NMI Approval (4,000 Divisions at 0.8 μ V/Division). C-tick Approval and CE Approval

Accuweigh Pty Ltd

WESTERN AUSTRALIA (HEAD OFFICE):
PHONE: (08) 9259 5535

SOUTH AUSTRALIA OFFICE:
PHONE: (08) 8447 5011

NEW SOUTH WALES (SYDNEY) OFFICE:
PHONE: (02) 9728 4877



www.accuweigh.com.au

VICTORIA OFFICE:
PHONE: (03) 9548 5554

NEW SOUTH WALES (NEWCASTLE) OFFICE:
PHONE: (02) 4966 8900

QUEENSLAND OFFICE:
PHONE: (07) 3265 5520